



- 01 **Efficient:** Water is applied slowly and directly to the plant
- 02 **Smart:** Flow options up to 6 GPH provide maximum flexibility
- 03 **Quality:** All Hunter PSEs are assembled in the USA

POINT SOURCE DRIP EMITTERS

The Right Amount of Water, Right at the Plant

Hunter emitters apply water slowly and directly at the plant to ensure every drop is put to efficient use. They come in three convenient styles including self-piercing barb, $\frac{1}{8}$ " threaded, and $\frac{1}{2}$ " female thread. The barb and $\frac{1}{8}$ " thread models are available in 0.5, 1, 2, 4, and 6 GPH models and the $\frac{1}{2}$ " female threaded models come in 1 and 2 GPH. This wide range of flow rates offers you the flexibility to give individual plants and trees the right amount of water from a single emitter. They are also color-coded for fast flow identification and feature coined edges for easy gripping during installation.

An optional diffuser cap is available to help gently distribute water at high GPH flow and to protect the emitter outlet from clogging. Manufactured by Hunter in the USA, these emitters offer the ability to enhance both water and operational efficiency in any micro-irrigation zone.

POINT SOURCE DRIP EMITTERS FEATURES & SPECIFICATIONS

Features

- Slowly delivers water right to the plant
- Available in three convenient styles
- Pressure compensating from 15–50 PSI
- Flow labeled in imperial and metric units
- Assembled in the USA
- Optional diffuser cap available
- Barbed emitters can be inserted into ½" and ¼" tubing without tools for fast installation

Advanced Features

- **Color Coded Inlet:** Models are color coded by flow rate for fast identification
- **Coined Edge for easy installation:** Ribbed edges provide easy tool-free installation
- **Array of flow rates:** With flow rates ranging from 0.5 to 6 GPH, plants can get the right amount of water from a single emitter

Operating Specifications

- Pressure compensating 15 to 50 PSI

DIFFUSER CAP

Gently distributes water at higher flows and protects the emitter outlet from clogging



POINT SOURCE EMITTERS – SPECIFICATION BUILDER

Model	Flow Rate	Inlet	Qty./Bag
HE	0.5, 1, 2, 4, 6 GPH	B = Self-piercing Barb	25/100
		T = 10/32 Threaded	25/100
HEB	1, 2 GPH	1/2" Female thread	25
HE	Diff = Diffuser/Bug Cap	Snap Fit	50

EMITTER MODEL CHART

		Model	Inlet Type	Flow (GPH)
	Blue	HE-050-B	Self-piercing Barb	0.5
	Black	HE-10-B	Self-piercing Barb	1.0
	Red	HE-20-B	Self-piercing Barb	2.0
	Tan	HE-40-B	Self-piercing Barb	4.0
	Orange	HE-60-B	Self-piercing Barb	6.0
	Blue	HE-050-T	10/32 Thread	0.5
	Black	HE-10-T	10/32 Thread	1.0
	Red	HE-20-T	10/32 Thread	2.0
	Tan	HE-40-T	10/32 Thread	4.0
	Orange	HE-60-T	10/32 Thread	6.0
	Black	HEB-10	1/2" Female Thread	1.0
	Red	HEB-20	1/2" Female Thread	2.0

Website hunterindustries.com | **Customer Support** 760-744-5240 | **Technical Service** 760-591-7383

Helping our customers succeed is what drives us. While our passion for innovation and engineering is built into everything we do, it is our commitment to exceptional support that we hope will keep you in the Hunter family of customers for years to come.

Gregory R. Hunter, President of Hunter Industries

